# -TRUCK600

# CHASSIS CAB



#### CHASSIS

Ladder type frame (for a maximum of safety) in aluminium high resistance (naturally anticorrosion)

#### CABIN AND DOORS

- Safe heavy duty aluminium cabin.
- Doors high resistance due to their aluminium structure
- ABS-PMMA Body (naturally anticorrosion)
- Automobile-type Door handles
- Central locking and electric windows

#### SAFETY AND ERGONOMICS

- Automatic (CVT type) transmission with steering lever on the dashboard
- Ergonomic driving and pedal position
- Seats with head rests
- Cabin very spacious (shoulder width 1 280 mm elbows width 1 170 mm)
- Multiple storage
- Easy access (height seats / floor 760 mm no wheel arch)
- Panoramic windscreen with wiper blades double,
- Seat belts
- Disks at the front
- Sun visors
- Rear protection bar
- LED daytime running lights

#### AUTOMOBILE TYPE DASHBOARD AND CONTROLS

#### ENGINE

- Traction
- KUBOTA diesel motor 600 cm3 liquid-cooled
- Power 11,2 kW at 3600 RPM- Couple 34 Nm at 2200 RPM
- Automatic speed controller and gearbox with differential

#### STEERING

Very flexible, rack and pinion steering

#### BRAKING

- Dual circuit with 220 mm disks at the front and 160 mm drums at the rear with load sensing valve,
- Automatic pad wear compensation,
- Mecanical handbrake on rear axle.

#### SUSPENSION

- FRONT: fully independent Mac Pherson-type struts, coil springs.
- REAR: independent trailing arm suspension with coil springs.

#### TYRES

145/70 R13







## STANDARD **EQUIPMENT**

Seat belts

Automatic activation of hazard lights on sudden braking

LED daytime running lights

Reversing light and fog rear light

Inside rearview mirror

Left and right outside rearview mirrors

Tinted windows

Cabin rear window

Interior lighting controlled by the door opening

Wiper with double blades - 3 speed (one intermittent speed)

Windscreen washer

2 sun visors

Ignition switch and steering lock

Lockable fuel tank cap

Horn

«Lights on» warning buzzer

Rear protection bar

Spare wheel and jack with key

Automobile-type dashboard

Maintenance indicator

Ashtray and cigarette lighter

Glove box

Shift lever steering ultra flexible

Cabin doors equipped with storage compartment

Seats with headrest

Roof with insulation inner panel

Rubber mat on floor flat

Heating-ventilation-powerful 2-speed fan

Radio pre-equipment

Wheel covers



### **PERFORMANCES**

**REGULATIONS** 

USAGE

**MAXIMUM SPEED** 

CONSUMPTION

**TANK** 

**CLIMBING CAPABILITY** 

**EMISSIONS OF CO.** 

HEAVY QUADRICYCLE

(European directive 2002/24/CE category L7e)

Passenger car driving licence or equivalent.

Age 16 depending on the country

75 kph (45 mph)

about 4,14 liters / 100 km

24 liters

slope more than 20% (with max load

108,9 g/km\*

\*Measurement according to cycle described in directive 97/24/CE modified 2006/27/CE





## OPTIONAL **EQUIPMENT**

#### **GENERAL OPTIONS**

Hook with lights connections and protection bar

#### **OPTIONS** COMFORT

**Electric pack:** electric windows and central locking

Radio

Additional heating system

#### **EQUIPMENT OPTIONS**

See model sheets

#### SAFETY OPTIONS

- > Side protection bars
- > Reflecting tapes class 1
- > Reflecting tapes class 2
- > Warning triangle + 2 beacon lights
- > Reverse bipper
- > Lashing rings
- > Beacon light




PICK-UP








**DROPSIDE** 











#### **DIMENSIONS (mm)**

FRONT TRACK WIDTH
REAR TRACK WIDTH
AVERAGE WHEEL BASE
FRONT OVERHANG
MINI/MAXI RIDEABLE REAR OVERHANG (X)
MINI/MAXI RIDEABLE LENGTH (Z)
MINI/MAXI EFFECTIVE LENGTH (Y)
OVERALL WIDTH
MAXIMUM RIDEABLE WIDTH (W)
CABIN HEIGHT (WITHOUT OPTIONS)
MAXI RIDEABLE HEIGHT (V**)

MINI/MAXI POSITION OF LOAD CENTRE OF GRAVITY IN RELATION TO THE AXIS OF THE FRONT AXLE: (U)

*	Hnladen	vehicle	+ 25	mm

<sup>\*\*</sup> Unladen vehicle in running order

1 345
1 273
2 330
426
364 / 944
3 120 / 3 700
1 532 / 2 112
1 500
1 500
1 750 ± 25
2 500
1 850 / 2 260





TIPPER

TOTAL AUTHORISED LADEN WEIGHT	1 000
MAX TOLERATED LOAD ON FRONT AXLE	475
MAX TOLERATED LOAD ON REAR AXLE	690
UNLADEN WEIGHT OF RUNNING ORDER CHASSIS CAB:	
TOTAL	420
ON FRONT AXLE	290
ON REAR AXLE	130
PAYLOAD OF RUNNING ORDER VEHICLE:	
CHASSIS CAB PAYLOAD*	580
PICK-UP PAYLOAD*	535
DROPSIDE PAYLOAD*	480
VAN PAYLOAD*	480
TIPPER PAYLOAD*	421
MAXIMUM TOWING CAPABILITY (BRAKED OR NOT BRAKED)	200
excluding driver, passenger, equipment, options and load	
OPTIONS WEIGHT (TO BE DEDUCTED FROM THE PAYLOAD)*	
SIDE PROTECTION BARS	12
HOOK WITH LIGHTS CONNECTIONS	10
ROOF LADDER RACK	16
FOLDING CAGE	40
HIGH CANVAS COVER	24



### **AVAILABLE COLORS**







AIXAM MEGA 56 ROUTE DE PUGNY BP 112 73101 AIX-LES-BAINS CEDEX FRANCE

TEL + 33 (0)4 79 61 42 45 FAX + 33 (0)4 79 35 06 11 MAIL mega@mega-vehicles.com

